

Product data sheet

Specifications

Rack PDU, Basic, 1U, 15A, 120V, (10)5-15



AP9562

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	100 V 120 V
PDU type	Basic
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Number of rack unit	1U
Cable length	3.66 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Physical

Colour	Black
Height	4.4 cm
Width	44.7 cm
Depth	5.7 cm
Net weight	2.5 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

Input

[In] rated current	12 A
Input current limits	15 A
Load capacity	1400 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets10 NEMA 5-15R

Conformance

Product certificationscUL listed
METI Denan
UL listed

Environmental

Ambient air temperature for operation-5...45 °C

Relative humidity0...95 %

Operating altitude0...10000 ft

Ambient air temperature for storage-25...65 °C

Storage Relative Humidity0...95 %

Storage altitude0.00...15240.00 m

Packing Units

Unit Type of Package 1PCE

Number of Units in Package 11

Package 1 Height7 cm

Package 1 Width22.9 cm

Package 1 Length46.4 cm

Package 1 Weight3.64 kg

Offer Sustainability

REACH Regulation[REACH Declaration](#)

EU RoHS DirectiveCompliant
[EU RoHS Declaration](#)

Lead freeYes

California proposition 65WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](#)

Optimized Energy EfficiencyEnergy efficient product

Take-backTake-back program available

Contractual warranty

Warranty2 years repair or replace

Recommended replacement(s)