Ortronics

6-LC (12 fibers) multimode aqua adapters with ceramic alignment sleeves

Part No. OFP-LCD12LC



The Ortronics OptiMo® OFP series adapter panels are used with our popular Q-Series modular fiber enclosures, offering great flexibility in structured cabling design. Front-removable adapter panels are available with LC, SC, ST, and MT-RJ adapters and feature options ideal for both single mode and multimode applications.

Features & Benefits

- Up to 72 LC fibers per RU
- Made of durable polycarbonate
- 6, 8, 12 & 24 port panels
- Utilizes Shuttered Adapters
- Available in, LC, SC, ST and blank styles
- Zirconia ceramic sleeves for optimal performance
- Color options available

Specifications

General Info

Product Line	Ortronics	Color	Aqua
UPC Number	662875629856	Country Of Origin	Mexico
Material	Thermoplastic	Product Type	Adapter Panel
Features	Shuttered	Included	Cover
Application Sector	Commercial, Data Center	Standard	TIA-568-C.3;RoHS Compliant
Warranty Type	5-Year		

Dimensions

Product Width US	5.12 in	Product Depth US	1.15 in
Product Height US	1.19 in		

Additional Information

Product Environmental Profile	Yes

Technical Information

Fiber Optic Cable Type	OM3, OM4	Operating Temperature Min	-10 °C
Compatibility	Q-Series SD Enclosure, RFP SD Panels	Number of Ports	12
Alignment Sleeve Material	Zirconia	Simplex/Duplex	Duplex
Polarity Type	Universal	Operating Temperature Max	60 °C
Shuttered Adapters	No	Single/Multimode	Multimode
Number of Fibers	12	Fiber Type	Multi-Mode
Connector 2	LC	Connector 1	LC
Form Factor	LC Duplex	Operating Temperature	-10°-60°C
Durability	500 matings	Operating Humidity	0-80% RH (Non-Condensing)
Connectivity Footprint	Q-Series Standard Density	Storage Temperature	-40° - 75° C