



- 80 Plus Bronze certified for high efficiency
- 120mm Low Noise Fan
- Industrial level protection with OVP,OCP,OPP,OTP, SCP
- DC-DC Circuit Design
- Active PFC design

SPECIFICATIONS

| | |
|------------------------------|-----------------------------|
| Efficiency Rating | 80 PLUS Bronze (up to 85%) |
| Modular | No |
| Fan Size | 120 mm |
| Fan Bearing | Sleeve Bearing |
| Dimensions (DxWxH) | 140 x 150 x 86 mm |
| PFC Type | Active PFC |
| Input Voltage Range | 100~240 VAC |
| Power Watt | 550W |
| Input Frequency Range | 50~60 Hz |
| Protection | OCP / OVP / OPP / OTP / SCP |
| ATX (24 pin) | 1 |
| EPS (4+4 pin) | 1 |
| PCI-E (6+2 pin) | 2 |
| SATA (15 pin) | 5 |
| PERIPHERAL (4 pin) | 2 |
| FDD (4 pin) | 1 |

MAG A550BN

| | | | | | |
|-------------|--------------------------|-------|-------|-------|-------|
| AC INPUT | 100-240V~, 8-4A, 50-60Hz | | | | |
| DC OUTPUT | +5V | +3.3V | +12V | -12V | +5Vsb |
| | 20A | 20A | 45.5A | 0.3A | 2.5A |
| TOTAL POWER | 110W | 546W | 3.6W | 12.5W | |
| | 550W | | | | |

CONNECTOR

| CONNECTOR | | | | | |
|------------------|-----|-------|------|------------|-----|
| ATX | EPS | PCI-E | SATA | PERIPHERAL | FDD |
| 1 | 1 | 2 | 5 | 2 | 1 |