

Technical Specifications

APC Home Office SurgeArrest 8 Outlet with Phone (Splitter) and Coax Protection, 120V | P8VT3 | Downloaded on 05/04/2021 (EST)



APC Home Office SurgeArrest 8 Outlet with Phone (Splitter) and Coax Protection, 120V P8VT3

Call for More Information 800-800-4272

- Includes: Coaxial cable, Cord management straps, Telephone cable, User manual

Output

Number of Outlets	8.0
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.8meters)
Number of Power Cords	1

Surge Protection and Filtering

Surge energy rating	2770Joules
Data Line Protection	Cable modem/video protection, RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines)
eP Joule Rating	2525
Data Lines Protected (multi-line only)	1-4

Physical

Maximum Height	1.26inches (32MM, 3.2CM)
Maximum Width	3.5inches (89MM, 8.9CM)
Maximum Depth	12.99inches (330MM, 33.0CM)
Net Weight	2.03lbs. (0.92KG)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Home Office SurgeArrest 8 Outlet with Phone (Splitter) and Coax Protection, 120V | P8VT3 | Downloaded on 05/04/2021 (EST)

Physical	
Shipping weight	2.43lbs. (1.1KG)
Shipping Height	2.36inches (60MM, 6.0CM)
Shipping Width	5.59inches (142MM, 14.2CM)
Shipping Depth	14.17inches (360MM, 36.0CM)
Color	Black
Master Carton Dimensions (Length x Width x Height)	15 x 8 x 12inches (381 x 203 x 305MM)
Master Carton Units	6.0
Master Carton Weight	16.49lbs. (7.48)
SCC Codes	10731304249044

Environmental	
Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA, UL 1363, UL 1449
Equipment protection policy	Lifetime : \$150000
Standard warranty	Lifetime

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.