



## A simple and reliable IP Phone

### GXP1610 • GXP1610P • GXP1615

A simple IP phone for small business users, the GXP1610/GXP1610P/1615 delivers a user-friendly VoIP calling experience in a very easy-to-use IP phone. The GXP1610/GXP1610P/1615 offers support for 2 lines, 2 call appearances and includes 3-way voice conferencing to maximize productivity. Additional features include a 132x48 (2.95") LCD screen for easy viewing, 3 XML programmable soft keys for customization, 10/100 mbps ports, integrated PoE on the GXP1610P/GXP1615 model, EHS support for Plantronics headsets and multi-language support. These features allow the GXP1610/GXP1610P/GXP1615 to be a high-quality small business IP phone that is simple and easy-to-use.



2 SIP accounts,  
up to 2 call  
appearances



TLS and SRTP  
security encryption  
technology to  
protect calls and  
accounts



3-way audio  
conferencing for easy  
conference calls



Electronic Hook Switch  
(EHS) support for  
Plantronics headsets



Automated  
provisioning  
options include  
TR-069 and XML  
config files



Full-duplex  
speakerphone  
with HD audio  
to maximize  
audio quality  
and clarity



Use with  
Grandstream's UCM  
series of IP PBXs  
for Zero Config  
provisioning



Built-in PoE 802.3af  
to power the device  
and give it a network  
connection (GXP1610P/  
GXP1615 only)

<b>Protocols/Standards</b>	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP, CDP/SNMP/RTCP-XR
<b>Network Interfaces</b>	Dual switched auto-sensing 10/100 Mbps Ethernet ports, integrated PoE (GXP1610P/GXP1615 only)
<b>Graphic Display</b>	132 x 48 (2.95") LCD display
<b>Feature Keys</b>	2 line keys with dual-color LED and 2 SIP accounts, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys. 13 dedicated function keys for PAGE/INTERCOM, PHONEBOOK, MESSAGE, HOME, HOLD, RECORD, MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME
<b>Voice Codexs</b>	Support for G.711 $\mu$ /a, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC
<b>Telephony Features</b>	Hold, transfer, forward (unconditional/no-answer/busy), 3-way conferencing, call park/pickup, downloadable phone book (XML, LDAP, up to 1000 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & fail-over
<b>Headset Jack</b>	RJ9 headset jack (allowing EHS with Plantronics headsets)
<b>Base Stand</b>	Yes, 2 angled positions available, wall mountable
<b>Wall Mountable</b>	Yes
<b>QoS</b>	Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS
<b>Security</b>	User and administrator level access control, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control
<b>Multi-language</b>	English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more
<b>Upgrade/Provisioning</b>	Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR-069 or AES encrypted XML configuration file, FTP/FTPS
<b>Power &amp; Green Energy Efficiency</b>	Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mA; PoE: IEEE802.3af Class 2, 3.84W-6.49W; IEEE802.3az (EEE) (GXP1610P/GXP1615 Only)
<b>Physical</b>	Dimension: 209mm (L) x 184.5mm (W) x 76.2mm (H) (with handset) Unit weight: 0.74kg; Package weight: 1.1kg (GXP1610/GXP1615) 1.0kg (GXP1610P)
<b>Temperature and Humidity</b>	Operation: 0°C to 40°C, Storage: -10°C to 60°C, Humidity: 10% to 90% Non-condensing
<b>Package Content</b>	GXP1610/GXP1610P/1615 phone, handset with cord, base stand, universal power supply (GXP1610/GXP1615 only), network cable, Quick Installation Guide, brochure, GPL License
<b>Compliance</b>	FCC: Part 15 (CFR 47) Class BCE : EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/NZS 60950.1