

SL-801UL

Line interactive smart UPS system with a multifunction LCD touchscreen display for real-time monitoring.



Forza's new SL series of smart UPS systems has been redesigned with a LCD touchscreen for ease of use through its user friendly interface which also displays power conditions in real time. The SL series counts with UL certification and is a complete solution for government agencies or private businesses in the educational, financing and public sectors. The integration of voltage regulation, surge suppression and backup capabilities in a single unit has made this one of the best-selling UPS systems in its class. The UPS comes with ForzaTracker monitoring software to easily administer the unit directly from your computer through a USB communication port. Long-lasting battery support along with complete power protection helps prevent data loss during mission critical operations.

Highlights

- Touch screen LCD status display
- USB communication port with monitoring software
- Overload, discharge and overcharge protection
- Fire retardant plastic
- UL and NOM certification



Ideal for

800VA
PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up

MPN	SL-801UL
General	
Capacity	800VA/480W
Input	
Nominal voltage	120V
Voltage range	89-145VAC
Frequency	45-65Hz (autosensing)
AC plug style	NEMA 5-15P
Output	
Nominal voltage	120V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz Battery mode
Waveform	Modified sine wave
Total outlets	6 (NEMA 5-15R)
Full battery with surge protection outlets	5
Surge protection only outlets	1
Network protection	RJ-45
Phone/modem/fax protection	RJ-11
USB management	Included with ForzaTracker software
Battery	
Battery type and quantity	12V/9Ah (1)
Backup time	32min**
Recharge time	4 hours to 90% after complete discharge
Voltage regulation	
High cutoff	145V +/- 5%
Boost 1	102-110V +/- 5%
Buck	125-138V +/- 5%
Low cutoff	89V +/- 5%
Frequency regulation	
Automatic frequency selection	Included
Line/battery transfer	
Typical transfer time	2-4ms
Low line transfer to battery	89VAC +/- 5%
High line transfer to battery	145VAC +/- 5%
Alarms/indicators	
Visual indicators (LCD display)	Easy to read touchscreen LCD with a blue backlight that displays input voltage, output voltage, battery capacity, load level, and UPS status
Audible tone	Battery mode: Sounds every 10 seconds Low battery: Sounds every second Overload: Sounds every 0.5 second Fault: Sounds Continuous sound
Protection	
Full protection	Voltage regulation, overload, discharge and overcharge protection
Joules	510J
Special Features	
"Cold start" option	Included
Auto charge	Included
Environment	
Operating temperature	32-104°F
Storage temperature	5-113°F
Relative humidity	0-90% non-condensing
Audible noise	<40dB at one meter

MPN	SL-801UL
Physical appearance	
Power switch	Push button
Housing	ABS fire retardant plastic
Color	Black
Dimensions	11.8x3.9x 5.6in
Weight	11lb
Additional information	
Warranty	3 years*

* 2 years on batteries
 ** Single PC plus monitor

