

Semi-knocked down fixed wallmount enclosure

6U/9U/12U/15U/18U - 450mm/600mm




<i>NPC-F6U64B</i>	<i>NPC-F9U66B</i>
<i>NPC-F9U64B</i>	<i>NPC-F6U66B</i>
<i>NPC-F12U64B</i>	<i>NPC-F12U66B</i>
<i>NPC-F15U64B</i>	<i>NPC-F15U66B</i>
<i>NPC-F18U64B</i>	<i>NPC-F18U66B</i>

Related products



AW220NXT07



AW220NXT21



AW220NXT95

Nexxt Solutions semi-knocked down (SKD) fixed wall mount enclosures are ideal for installations where space is limited or a full cabinet solution is not required. These wallmount units are housed in a lockable heavy-gauge metal enclosure, to keep network equipment and cables safe and properly organized. Each cabinet includes a fan tray to ensure optimum ventilation inside the unit. Available with 6, 9, 12, 15 and 18 rack spaces, these enclosures are designed for mounting multiple patch panels and diverse network, voice and data devices. Easy to install and assemble, our wallmount cabinets offer a cost-effective solution for applications requiring flexibility, security, and cable management capabilities.

Main features

- 132lb maximum static load capacity
- Frame construction reinforced with steel, specially made to support heavy equipment
- Lockable access to front glass door
- Convenient side panels are easy to remove for maintenance
- Standard square-punched mounting rails for faster equipment loading
- The front door can turn 270 degrees
- Top tray with space for two optional fan units provides outstanding ventilation to avoid overheating
- Toolless, reversible glass door installation
- EIA-compliant mounting rail system can be easily adjusted to accommodate equipment of varying depths
- U-rack units numbered on the front and back sections simplify installation
- Finished surface prevents damage caused by rust and other external factors

www.nexxtsolutions.com

Nexxt Solutions® ("Nexxt") is a registered trademark. Nexxt reserves the right to change any specifications without prior notice. The information contained in this product sheet is the proprietary property of Nexxt, and may not be used, reproduced or disclosed to others, in whole or in part, without written authorization of Nexxt. Although Nexxt has taken precautions to ensure the accuracy of the product specifications at the time of publication, however, we cannot be responsible for the errors, omissions, or changes due to obsolescence. If you would like to know more about our products, please visit our website at www.NexxtSolutions.com.

Semi-knocked down fixed wallmount enclosure

6U/9U/12U/15U/18U - 450mm/600mm

Technical specifications 450mm

Wall mount enclosure characteristics					
Color	Black varnish paint (RAL 9005)				
Effective U space	6U	9U	12U	15U	18U
Structure type	Semi-knocked down (SKD)				
Mounting type	Wall mounted, fixed				
Access type	Side removable panels Front door and rear panel				
Material (main body)	SPCC*, 19 gauge				
Material (mounting angles)	SPCC*, 16 gauge				
Ventilation access	Space for 2 ventilation units (optional fans available)				
Protection grade	IP20				
Dimensions					
External height	14.57in/370mm	14.57in/370mm	25in/635mm	30.31in/770mm	35.63in/905mm
Internal height	10.55in/268mm	10.55in/268mm	20.98in/533mm	27.09in/668mm	31.61in/803mm
External width	23.62in/600mm				
Internal width	19in/483mm				
External depth	17.72in/450mm				
Max. device depth	12.95in/329mm				
Static load capacity	132lb/60kg				
Dynamic load capacity	00lb/ 00kg				
Front door spin degree	Can turn up to XXX degrees				
Includes	1 top panel 1 bottom panel 2 frames 1 front glass door 1 rear panel 2 side panels 2 L-shaped brackets 1 mounting bracket 4 vertical rails Assembly hardware kit Equipment mounting hardware kit User manual				
Certifications and standards					
International standards	CE				
Certifications and approvals	RoHs, Reach				
Miscellaneous					
MPN	NPC-F6U64B	NPC-F9U64B	NPC-F12U64B	NPC-F15U64B	NPC-F18U64B
UPC					
Labeling	NEXXT SOLUTIONS				
Packaging	Carton box				
Cu.ft					
Warranty	5-year limited warranty**				

*SPCC: Commercial grade, cold rolled steel sheets

** For warranty details, visit www.nexxtsolutions.com/warranty

Semi-knocked down fixed wallmount enclosure

6U/9U/12U/15U/18U - 450mm/600mm

Technical specifications 600mm

Wall mount enclosure characteristics					
Color	Black varnish paint (RAL 9005)				
Effective U space	6U	9U	12U	15U	18U
Structure type	Semi-knocked down (SKD)				
Mounting type	Wall mounted, fixed				
Access type	Side removable panels Front door and rear panel				
Material (main body)	SPCC*, 19 gauge				
Material (mounting angles)	SPCC*, 16 gauge				
Ventilation access	Space for 2 ventilation units (optional fans available)				
Protection grade	IP20				
Dimensions					
External height	14.57in/370mm	19.69in/500mm	25in/635mm	30.31in/770mm	35.63in/905mm
Internal height	10.55in/268mm	15.67in/398mm	20.98in/533mm	27.09in/668mm	31.61in/803mm
External width	23.62in/600mm				
Internal width	19in/483mm				
External depth	23.62in/600mm				
Max. device depth	18.82in/479mm				
Static load capacity	132lb/60kg				
Dynamic load capacity	00lb/ 00kg				
Front door spin degree	Can turn up to XXX degrees				
Includes	1 top panel 1 bottom panel 2 frames 1 front glass door 1 rear panel 2 side panels 2 L-shaped brackets 1 mounting bracket 4 vertical rails Assembly hardware kit Equipment mounting hardware kit User manual				
Certifications and standards					
International standards	CE				
Certifications and approvals	RoHs, Reach				
Miscellaneous					
MPN	NPC-F6U66B	NPC-F9U66B	NPC-F12U66B	NPC-F15U66B	NPC-F18U66B
UPC					
Labeling	NEXXT SOLUTIONS				
Packaging	Carton box				
Cu.ft					
Warranty	5-year limited warranty**				

*SPCC: Commercial grade, cold rolled steel sheets
** For warranty details, visit www.nexxtsolutions.com/warranty

