

Specifications



Eaton PDUV15

Eaton Tripp Lite series basic PDU, 1PH, 0U, NEMA 5-15P input, 15 ft cord, 1.4kW, 12A, 120V, 14 outlets (14) 5-15R

General specifications

PRODUCT NAME	Eaton Tripp Lite series basic PDU
CATALOG NUMBER	PDUV15
UPC	037332144515
PRODUCT LENGTH/DEPTH	1.25 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	36 in
PRODUCT WEIGHT	3.3 lb
COMPLIANCES	RoHS TAA Compliant FCC Class A CE Marked
CERTIFICATIONS	UL 60950-1 CSA Std. C22.2 NOM
GLOBAL CATALOG	PDUV15
PRODUCT TYPE	Basic PDU

Product specifications

FORM FACTOR	0U (Vertical)
PHASE	Single-phase
AMPERAGE RATING	12A
INPUT CONNECTION	NEMA 5-15P
CORD LENGTH	15 ft
FREQUENCY RATING	50/60 Hz
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
TAA COMPLIANCE	No

Resources

	120V Power Distribution Unit (PDU) Models and Specifications List (English)
	230V Power Distribution Unit (PDU) Brochure (English)
BROCHURES	120V PDU Brochure Specifications (Spanish)
	120V Power Distribution Unit (PDU) Brochure (English)
	Integrated Solutions Brochure (English)
DRAWINGS	Single-Phase Power Distribution Units (PDUs) Stencil Preview
MANUALS AND USER GUIDES	Owner's Manual for Select Rackmount PDUs

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

