

FX-2200LCD

The Forza FX Series offers an enhanced level of protection, specially designed for your high-performance office equipment and entertainment components.



It features a coaxial surge protection line and LCD display, in addition to a battery-supported system (UPS), allowing you ample time to save your important information and shut down all your equipment safely during power failures. The FX UPS system comes in two different configurations: 1500VA and 2200VA.

Highlights

- Smart UPS with line interactive topology
- Emergency backup power supply
- Complete AVR protection
- System monitoring made simple with a state-of-the-art LCD display
- Coaxial line protection
- Gigabit protection for networking, VoIP communication and modem devices
- ForzaTracker software
- USB cable included
- Trusted quality
- Backed by a 3-year warranty, limited to 2 years on batteries



Ideal for

2200VA

PROTECTION LEVEL 5

- + Breaker
- + Surge protector
- + Voltage protector
- + Voltage regulator
- + Power back up

MPN

FX-2200LCD

MPN	FX-2200LCD
General	
Capacity	2200VA/1200W
Input	
Nominal voltage	120V
Voltage range	89-145VAC
Frequency	45-65Hz (autosensing)
AC plug style	NEMA 5-15P
Output	
Nominal voltage	120V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz battery mode
Waveform	Modified sine wave
Total outlets	8 (NEMA 5-15R)
Full battery / Surge protection outlets	6
Surge protection outlets only	2
Network protection	RJ-45 (supports gigabit speeds)
Phone/modem/fax protection	RJ-11
Coaxial protection	Included
USB management	Included
Battery	
Type and quantity	12V/9Ah (2)
Backup time	81 min **
Recharge time	6 hours to 90% after complete discharge
Voltage regulation	
Automatic voltage regulation	Included
Frequency regulation	
Automatic frequency selection	Included
Line/Battery transfer	
Typical transfer time	2-4ms
Low line transfer to battery (120/220V)	89VAC
High line transfer to battery (120/220V)	145VAC
Alarms/Indicators	
Visual indicators	Easy to read LCD with a blue backlight that displays the battery status, input voltage, output voltage, and operation mode of the UPS
Audible	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound
Protection	
Full protection	Line mode: 110%+20%/-10%; shuts down after 5 minutes and goes to fault mode. 120%+20%/-10%; shuts down immediately and goes to fault mode Battery mode: 120%+20%/-10%; shuts down immediately
Joules	660J
Special features	
"Cold start" option	Included
Auto charge	Included
Environment	
Operating temperature	32-104° F
Storage temperature	5-113° F
Relative humidity	0-90% non-condensing
Audible noise	<40 dB at one meter

MPN	FX-2200LCD
-----	------------

Physical appearance	
Power switch	Included (lighted)
Housing	Flame retardant plastic
Color	Black
Cord length	3ft
Dimensions	15.3x5.6x7.7in
Weight	25lb
Additional information	
Warranty	3 years*

*2 years on batteries
 **Calculated with a single PC plus monitor at 7% load



Forza Power Technologies® is a registered trademark. Other company and product names mentioned herein are trademarks of their respective owners. Mention of third-party products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Forza Power Technologies® assumes no responsibility with regards to the performance or use of these products. Made in China.