## Key **Features**

Stunning Ultra HD resolution | Next generation connectivity | View up to four video sources | Ergonomic Design




## Product **Description**

The ViewSonic® VG2860mhl-4K 28" Ultra HD LED monitor delivers stunning definition, ergonomic design, and future-proof connectivity for the ultimate work environment. Featuring a 3840x2160 ultra-high resolution panel, this monitor displays vivid, detailed images with 4-times the pixel density of conventional Full HD monitors. Future-proof connectivity options include DisplayPort® 1.2a, HDMI®, DVI, and 4-USB ports for flexible connectivity to a variety of applications ranging from document editing to reviewing detailed graphics. ViewSonic's MultiPicture™ functionality allows for efficient multitasking by providing simultaneous viewing of up to four split windows, while full ergonomic functionality delivers maximum comfort and enhanced productivity. With an energysaving Eco-mode feature, the VG2860mhl-4K delivers great power savings while boosting productivity for a variety of business applications.



Weight (imperial):



**DISPLAY** 

Mount:

VESA Compatible:

Frequency Horizontal:

Frequency Vertical:

Video Signal:

Video Input:

Analog Sync:

**Ergonomics:** 

Height Adjust:

Pivot (Right/Left):

Tilt (Forward/Back):

Swivel:







| Display:   |   |
|--|---|
| Display Size (in.):  | 28  |
| Panel Type:  | TN  |
| Resolution:  | 3840 x 2160   |
| Static Contrast Ratio:   | 1,000:1   |
| Light Source:  | LED   |
| Brightness:  | 300 cd/m2   |
| Response Time (Typical GTG):   | 2ms   |
| Viewing Angles:  | 170° horizontal, 160° vertical  |
| Backlight Life (Hours):  | 30,000  |
| Panel Surface:   | 3H Anti-glare, hard-coating   |
| Compatibility:   |   |
| PC Resolution (max):   | 3840 x 2160   |
| Mac® Resolution (max):   | 3840 x 2160   |
| Connector:   |   |
| USB 2.0 Type A(2), USB 2.0 Type B(1), 3.5mm Audio Out(1), HDMI In(2), DV | , USB 3.0 Type A(2), 3.5mm Audio In(1),<br>'I-D(1), Display Port(1), Mini Display Port(1)   |
| Audio:   |   |
| Internal Speakers:   | 3-watt (x2)   |
| Power:   |   |
| Eco Mode (Conserve):   | 28W   |
| Eco Mode (optimized):  | 34W   |
| Consumption (typical):   | 48W   |
| Consumption (max):   | 56W   |
| Voltage:   | AC 100-240V (universal), 50-60Hz  |
| Additional Hardware:   |   |
| Kensington Lock Slot:  | 1   |
| Controls:  |   |
| Physical Controls:   | 1, 2, Down, Up, Power   |
| On Screen Display:   | Auto Image Adjust, Contrast/Brightness,<br>Input Select, Audio Adjust, Color Adjust,<br>Information, Manual Image Adjust, Setup<br>Menu, Memory Recall (See user guide for<br>complete OSD functionality) |
| <b>Operating Conditions:</b>   |   |
| Humidity (non-condensing):   | 10-90%  |
|  |   |

100 x 100 mm

24~160kHz

150 mm / 5.9 in

350°

900/00

5° / 37°

Separate Sync, Composite Sync, Sync on Green

24~75Hz

|     | Net (lbs):  | 17.2                 |  |
|-----|---|----------------------|--|
|     | Net Without Stand (lbs):  | 11.7                 |  |
|     | Gross (lbs):  | 22.5                 |  |
|     | Weight (metric):  |                      |  |
|     | Net (kg):   | 7.8                  |  |
|     | Net Without Stand (kg):   | 5.3                  |  |
|     | Gross (kg):   | 10.2                 |  |
|     | Dimensions (imperial) (WxHxD):  |                      |  |
|     | Packaging (in.):  | 29.2 x 19.4 x 7.7    |  |
|     | Physical (in.):   | 26.0 x 19.0 x 10.5   |  |
|     | Physical Without Stand (in.):   | 26.0 x 15.4 x 1.9    |  |
|     | Dimensions (metric) (WxHxD):  |                      |  |
|     | Packaging (mm):   | 742 x 493 x 196      |  |
|     | Physical (mm):  | 659.7 x 483.4 x 266  |  |
| 1)  | Physical Without Stand (mm):  | 659.7 x 391.0 x 49.3 |  |
| 1 / | General:  |                      |  |
|     | Regulations: CE, CB, RoHS, ErP, REACH, WEEE, WHQL, Windows8, cULus, FCC-B, Mexico Energy, EAC, Ukraine, GS, Ergo  |                      |  |
|     | PACKAGE CONTENTS: VG2860mhl-4K monitor, Power cable, DisplayPort cable, Audio cable, USB 3.0 cable, Quick Start Guide, ViewSonic Wizard CD (with user guide)  Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Warranty: Three-year limited warranty on parts, labor and backlight |                      |  |
|     |   |                      |  |
|     |   |                      |  |
|     | UPC: 766907774115   |                      |  |
|     | Accessories:  |                      |  |
|     | CB-00008187, CB-00008948, CB-00010555, CB-00010684, CB-00010958, LCD-CABLE-001, LCD-CMK-001, LCD-EE-27-03, LCD-EEEW-27-01, LCD-EEEW-27-02, LCD-EW-27-01, LCD-EW-27-02, LCD-EW-27-03, LCD-WMK-001, VSPF2800  |                      |  |
|     | Awards:   |                      |  |



