


## Key Features

Full HD 1080p Resolution | Enhanced Viewing Comfort | The Power of HDMI | Dual Integrated Speakers



## Product Description

The ViewSonic® VA2446mh-LED is a 24" (23.6" viewable) widescreen monitor with a LED backlight and a glossy, thin-bezel design ideal for use in the home or at the office. With Full HD 1920x1080 resolution and a 50M:1 MEGA Dynamic Contrast Ratio, the VA2446mh-LED delivers stunning brightness and contrast, while a quick 5ms response time ensures crisp pictures and smooth playback. As a complete multimedia package, the display also includes a pair of integrated speakers. VGA and HDMI inputs provide flexible and convenient connectivity, while a VESA-compatible mount offers additional flexibility. With an efficient LED backlight and energy-saving Eco-mode, the VA2446mh-LED is an environmentally friendly display choice. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies provides great value for the stylish, high-performance VA2446mh-LED display.



### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

Display:

|                              |                                |
|------------------------------|--------------------------------|
| Display Size (in.):          | 24                             |
| Viewable Area (in.):         | 23.6                           |
| Panel Type:                  | MVA                            |
| Resolution:                  | 1920 x 1080                    |
| Static Contrast Ratio:       | 3,000:1                        |
| Dynamic Contrast Ratio:      | 50,000,000:1                   |
| Light Source:                | LED                            |
| Brightness:                  | 300 cd/m2                      |
| Colors:                      | 16.7M                          |
| Color Space Support:         | (6-Bit+HI-FRC)                 |
| Aspect Ratio:                | 16:9                           |
| Response Time (Typical GTG): | 5ms                            |
| Viewing Angles:              | 178° horizontal, 178° vertical |
| Backlight Life (Hours):      | 40,000                         |
| Panel Surface:               | Anti-glare, Hard coating (3H)  |

Compatibility:

|                        |             |
|------------------------|-------------|
| PC Resolution (max):   | 1920 x 1080 |
| Mac® Resolution (max): | 1920 x 1080 |

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), HDMI 1.4 In(1)

Audio:

|                    |           |
|--------------------|-----------|
| Internal Speakers: | 2.5W (x2) |
|--------------------|-----------|

Power:

|                        |                                  |
|------------------------|----------------------------------|
| Eco Mode (Conserve):   | 17W                              |
| Eco Mode (optimized):  | 21W                              |
| Consumption (typical): | 26W                              |
| Consumption (max):     | 28W                              |
| Voltage:               | AC 100-240V (universal), 50-60Hz |
| Stand-by:              | 0.5W                             |

Additional Hardware:

|                       |   |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

Controls:

|                    |  |
|--------------------|--|
| Physical Controls: | 1, 2, 3, 4, Power  |
| On Screen Display: | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |

Operating Conditions:

|                            |                       |
|----------------------------|-----------------------|
| Temperature:               | 32-104° F (0 - 40° C) |
| Humidity (non-condensing): | 20-90%                |

Mount:

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

Video Signal:

|                       |            |
|-----------------------|------------|
| Frequency Horizontal: | 24 ~ 82KHz |
| Frequency Vertical:   | 50 ~ 75Hz  |

Video Input:

|               |      |
|---------------|------|
| Digital Sync: | TMD5 |
|---------------|------|

Ergonomics:

|                      |          |
|----------------------|----------|
| Tilt (Forward/Back): | 5° / 22° |
|----------------------|----------|

Weight (imperial):

|                          |      |
|--------------------------|------|
| Net (lbs):               | 9.02 |
| Net Without Stand (lbs): | 8.1  |
| Gross (lbs):             | 12.0 |

Weight (metric):

|                         |     |
|-------------------------|-----|
| Net (kg):               | 4.1 |
| Net Without Stand (kg): | 3.7 |
| Gross (kg):             | 5.4 |

Dimensions (imperial) (WxHxD):

|                               |                   |
|-------------------------------|-------------------|
| Packaging (in.):              | 24.6 x 16.9 x 4.7 |
| Physical (in.):               | 22.3 x 15.7 x 8.3 |
| Physical Without Stand (in.): | 22.3 x 13.6 x 1.9 |

Dimensions (metric) (WxHxD):

|                              |                       |
|------------------------------|-----------------------|
| Packaging (mm):              | 624.0 x 429.0 x 118.0 |
| Physical (mm):               | 566.4 x 397.4 x 211.2 |
| Physical Without Stand (mm): | 566.4 x 346.3 x 48.0  |

General:

Regulations: cULus, FCC-B, ICES003, Energy Star, EPEAT, Mexico Energy, MX-CoC, CE, REACH, WEEE, eAC, UkrSEPRO

PACKAGE CONTENTS: LCD Display, Power Cable , VGA Cable , Audio Cable , Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907911763

Accessories:

CB-00008948, CB-00009950, LCD-DMA-001, LCD-DMA-002, LCD-EE-24-03, LCD-EEEW-24-01, LCD-EEEW-24-02, LCD-EW-24-01, LCD-EW-24-02, LCD-EW-24-03, LCD-WMK-001

