



CS850XTK08

Power supply w/ SATA | 700 Watts

Highlights

- Efficient PSU with temperature control fan
- ATX 12V compliant for all kinds of CPU and mainboard
- Selectable 115VAC and 230VAC operation

Specifications

General

| | |
|----------------------------|--|
| Connectors | 20+4PIN Cable, P4 2x Molex (IDE) + 2 x SATA 1x FDD |
| Power (in Watts) | 700W |
| ATX12V version | V2.2 |
| EPS12V version | N/A |
| MTFB | 30000 hours of continuous operation at 25 DC Full load, 75% confidence limit and normal line |
| Safety protection | Over Voltage Protection/ Over Current Protection/ Over Power Protection/ Short-circuit protection |
| Operating temperature (°C) | 0 to +40°C |
| Storage temperature (°C) | -20 to +85 °C |
| Operating humidity | 20% to 80% RH |
| Storage humidity | 10% to 90% RH |

AC input specs

| | |
|----------------------|--|
| Input voltage (VAC) | 115VAC or 230VAC (Selectable switch) |
| Input current (A) | 5A RMS MAX. for 115VAC & 3A RMS MAX. for 230VAC |
| Input Frequency (Hz) | 47-63Hz |

DC output specs

| | |
|-----------|------|
| +12V (A) | 45A |
| +3.3V (A) | 28A |
| +5V (A) | 38A |
| +5Vsb (A) | 2A |
| -12V (A) | 0.8A |

Cooling

| | |
|-----------------|---------|
| Fan included | 1 |
| Fan size (mm) | 80mm |
| Fan speed (RPM) | 2400RPM |

Additional information

| | |
|-----------------|--------------------|
| Package content | PSU and power cord |
| Cable length | 3.9ft |
| Dimensions | 5.9x 3.9 x 3.3in |
| Weight | 1.54lb |

